

Features	Test Method	Value
Length and Width	ISO 10545 - 2	16 x 300
Thickness		9mm
Surface Quality		100%
Water Absorption	ASTM C373	> 10%
Modulus of Rupture / Bending Strength	ISO 10545 - 4	1000 - 1250N
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	<5.5 x 10 ⁻⁶ °C ⁻¹
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	A
Chemical Resistance (Low Concentration)		B
Chemical Resistance (High Concentration)		B
Fire Resistance	-	A1/A1 _{FL}
Recycled Content	-	≤ 43%
Environmental Product Declaration	-	Industry Wide
Declared	-	Red List Free





This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Tile
- Gloss Finish
- 9.5mm Thickness
- Pressed Edge
- V1 - Uniform Appearance
- Not Resistant


www.genrose.com