

Features	Test Method	Value		
Water Absorption	ISO 10545-3	< 0.5%		
Flexion Resistance	ISO 10545-4	≥ 59 N/mm ²		
Abrasion Resistance (PEI)	ISO 10545-7	White	Grey	Blue
		IV	III	III
Thermal Shock Resistance	ISO 10545-9	Resistant		
Cracking Resistance	ISO 10545-11	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Acid Resistance	ISO 10545-13	GLA		
Alcalis Resistance		GLA		
Resistance to Cleaning Products		GA		
Resistance to Chemical Products to Pool Water		GA		
Stain Resistance	ISO 10545-14	5		
Size, Thickness, Side Straightness, Flatness, Orthogonality	-	Meets Requirements		
Hardness (Mohs)	Scratch Test (No regulated)	5		
DCOF	ANSI A137.1	0.59		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Natural Finish
- 10mm Thickness
- Rectified Edge
- PEI Rating = 3 (Blue, Grey) | 4 (White)
- V2 - Slight Shading Variation
- Frost Resistance = Yes

