

Features	Test Method	Value
Length and Width	ISO 10545-2	±0.6% (±2.00 MM)
Thickness		±5% (±0.5 MM)
Warpages of Edges		±0.5% (±1.5 MM)
Wedging		±0.5% (±2.00 MM)
Flatness		±0.5% (±2.00 MM)
Water Absorption	ISO 10545-3	≤ 0.5
Bending Strength	ISO 10545-4	R ≥ 35N/MM <sup>2</sup>
Breaking Strength		S > 1300 N
Linear Thermal Expansion Between 20° and 100°	ISO 10545-8	≈ 7X10 <sup>-6</sup> C <sup>-1</sup>
Thermal Shock Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Resistant
Color Resistant To Light	DIN 51094	No Alteration
Stain Resistance	ISO 10545.14	≥ Class 3
DCOF (WET)	ANSI 137.1-2012	Matte: > 0.42
Recycled Content	-	≥ 10%

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte | Polished Finishes
- 9.5mm | 9mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes

