



Features	Test Method	Value
Length and Width	ISO 1054-2	±0.5% mm
Thickness		7.5mm   8mm   10.5mm
Straightness of Sides		±0.5mm
Surface Flatness		±0.3%
Surface Quality		≥95%
Water Absorption	ISO 10545-3	E>10%
Modulus of Rupture / Bending Strength	ISO 10545-4	>15N/MM <sup>2</sup>
Breaking Strength		>600N
Scratch Hardness	ISO 10545-7	4 Mohs
Thermal Shock Resistance	ISO 10545-11	Resistant
Crazing Resistance	ISO 10545-12	Resistant
Chemical Resistance	ASTM C1378	Domestic - A
		Low Concentration - LA
Stain Resistance	ANSI A137.1	5
Recycled Material	-	6% Preconsumer
<div>   </div> <p>             This product will contribute to USGBC registered LEED projects.              It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.              Low Emissions Material • Zero VOC           </p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Ceramic Tile
- Matte Finish
- 7.5mm | 8mm | 10.5mm Thicknesses
- Pressed Edge
- V1 - Uniform Appearance
- Frost Resistance = No


[www.genrose.com](http://www.genrose.com)