

Features	Test Method	Value
Thickness	ASTM C499	± 0.03"
Surface Quality		Min. 95% of surface free of visible defects
Warpage	ASTM C485	Compliant
Wedging	ASTM C502	Compliant
Water Absorption	ASTM C373	≤ 0.5%
Breaking Strength	ASTM C648	≥ 350 lbf
Thermal Shock Resistance	ASTM C484	Resistant
Crazing Resistance	ASTM C424	Resistant
Fire Resistance	-	A1/A1fl
Slip Resistance (Wet)	ANSI A326.3	DCOF 0.71
VOC Emissions	-	Zero VOC
LEED	-	Yes
Recycled Content	-	40%
Greenguard Gold	-	Yes
Declare	-	Red List Free



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Applications:** Residential and Light Commercial

**Product Info:**

- Glazed Porcelain Tile
- Matte Finish
- 8mm Thickness
- Pressed Edge
- V3 - Moderate Variation
- Frost Resistant



[www.genrose.com](http://www.genrose.com)