

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.4 % mm
Thickness		± 0.5 mm
Surface Quality		Min. 95% of surface free of visible defects
Rectangularity		± 0.4% mm
Straightness of Sides		± 0.4 % mm
Water Absorption	ISO 10545-3	10% < Ev ≤20%
Breaking Strength	ISO 10545-4	> 600N
Modulus of Rupture	ISO 10545-4	≥ 15 N/mm ²
Coefficient of Linear Thermal Expansion	ISO 10545-8	≤7MK-1
Thermal Shock Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Not Resistant
Chemical Resistance (Domestic)	ISO 10545-13	A
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		HA
Stain Resistance	ISO 10545-14	Class 5
Slip Resistance	ANSI A326.3	DCOF Does Not Pass
Recycled Material	-	20% (Does not apply to deco)
VOC Emissions	-	Zero VOC
Declare	-	Red List Free
Health Product Declaration	-	Available


Declare.

This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Tile
- Matte Finish
- 8.5mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = No


www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.