

Features	Test Method	Value
Dimension	ISO 10545 - 2	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage		Compliant
Wedging		Compliant
Water Absorption	ISO 10545 - 3	$12\% < E < 18\%$
Modulus of Rupture / Bending Strength	ISO 10545 - 4	12 N/mm ²
Breaking Strength		600N
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	$6.5 \cdot 10^{-6} \text{ K}^{-1}$
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	A
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		$\geq \text{HB}$
Fire Resistance	-	A1/A1 _{FL}
Recycled Content	-	35%
LEED	-	Yes
VOC Emissions	-	Zero VOC
Environmental Product Declaration	-	Product Specific





This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Tile
- Matte Finish
- 9.8mm Thickness
- Rectified Edge
- V2 - Slight Variation (Natural)
- V3 - Moderate Variation (Other Colors)
- Not Frost Resistant


www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.