

Features	Test Method	Value
Dimensions and Appearance	ISO 10545-2	Prospect L.1
Water Absorption	ISO 10545-3	>10%
Flexural Resistance	ISO 10545-4	>17 N/mm ²
Modulus of Rupture		≥ 7.5 mm: min. 600 N < 7.5 mm: min. 200 N
Deep Abrasion Resistance	ISO 10545-6	-
Linear Expansion Thermic Coefficient	ISO 10545-8	≤ 7x10 ⁻⁶ °C ⁻¹
Resistance to Sudden Temperature Changes	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	-
Household Chemicals	ISO 10545-13	min. B
Low Concentration Alkalis		Available on Request
High Concentration Alkalis		Available on Request
Stain Resistance GL	ISO 10545-14	min. 3

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Wall Tile
- Matte Finish
- 10mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = No


www.genrose.com

Features	Test Method	Value
Dimensions and Appearance	ISO 10545-2	Prospect G.1
Water Absorption	ISO 10545-3	< 0.1%
Flexural Resistance	ISO 10545-4	> 45 N/mm ²
Modulus of Rupture		≥ 7.5 mm: min. 1300N < 7.5 mm: min. 700 N
Deep Abrasion Resistance	ISO 10545-6	< 140 mm ³
Linear Expansion Thermic Coefficient	ISO 10545-8	≤ 7x10 ⁻⁶ °C ⁻¹
Resistance to Sudden Temperature Changes	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	-
Frost Resistance	ISO 10545-12	Resistant
Household Chemicals	ISO 10545-13	min. B
Low Concentration Alkalis		From LA. LB TO LC
High Concentration Alkalis		Available on Request
Stain Resistance GL	ISO 10545-14	min. 3

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte | Outdoor Finishes
- 10mm | 20mm Thicknesses
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes


www.genrose.com