

Features	Test Method	Value
Length and Width	ISO 10545 - 2	±.5%
Thickness		±5%
Straightness of Sides		±5%
Rectangularity		±5%
Surface Flatness		±5%
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption		ISO 10545 - 3
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	GA
Chemical Resistance (Low Concentration)		GLA
Chemical Resistance (High Concentration)		GHA
Fire Resistance	-	A1/A1 _{FL}
Recycled Content	-	100%
Slip Resistance	ANSI A326.3	DCOF 0.51
LEED	-	Yes
VOC Emissions	-	Zero VOC



This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glass Tile
- Natural Finish
- 5.5mm | 5.6mm Thicknesses
- Pressed Edge
- V1 - Uniform Appearance (White | Vanilla | Almond | Velvet | Sage | Pine | Indigo | Black)
- V2 - Slight Variation (Glare | Candle | Wing | Ink | Plume | Chimney | Moon | Ginger | Platinum | Sky | Lilac)
- Frost Resistant

