

| Features  | Test Method    | Value                                     |                        |               |
|---|----------------|---|------------------------|---------------|
| <b>Dimensions</b>                               | ISO 10545 - 2  | Compliant                                 |                        |               |
| <b>Surface Quality</b>                          |                | Min. 95% of tiles free of visible defects |                        |               |
| <b>Water Absorption</b>                         | ISO 10545 - 3  | ≤ 0.1%                                    |                        |               |
| <b>Breaking Strength</b>                        | ISO 10545 - 4  | <b>Matte   Anti-Slip</b>                  | <b>Pavers</b>          |               |
|   |                | ≥ 1500 N                                  | ≥ 10000 N              |               |
|   |                | ≥ 40 N/mm <sup>2</sup>                    | ≥ 45 N/mm <sup>2</sup> |               |
| <b>Bending Resistance</b>                       |                |   |                        |               |
| <b>Deep Abrasion Resistance</b>                 | ISO 10545 - 6  | ≤ 150 mm <sup>3</sup>                     |                        |               |
| <b>Coefficient of Linear Thermal Expansion</b>  | ISO 10545 - 8  | ≤ 7 MK <sup>-1</sup>                      |                        |               |
| <b>Thermal Shock Resistance</b>                 | ISO 10545 - 9  | Resistant                                 |                        |               |
| <b>Crazing Resistance</b>                       | ISO 10545 - 12 | Resistant                                 |                        |               |
| <b>Chemical Resistance (Domestic)</b>           | ISO 10545 - 13 | A   |                        |               |
| <b>Chemical Resistance (Low Concentration)</b>  |                | LA  |                        |               |
| <b>Chemical Resistance (High Concentration)</b> |                | HA  |                        |               |
| <b>Fire Resistance</b>                          | -              | A1/A1 <sub>FL</sub>                       |                        |               |
| <b>Slip Resistance (Wet)</b>                    | ANSI A326.3    | <b>Matte</b>                              | <b>Anti-Slip</b>       | <b>Pavers</b> |
|   |                | DCOF 0.67                                 | DCOF 0.78              | DCOF 0.74     |
| <b>LEED</b>                                     | -              | Yes                                       |                        |               |
| <b>Recycled Material</b>                        | -              | 10%                                       |                        |               |
| <b>Environmental Product Declaration</b>        | -              | Product-Specific                          |                        |               |
| <b>Health Product Declaration</b>               | -              | Available                                 |                        |               |
| <b>Declare</b>                                  | -              | Red List Free                             |                        |               |
| <b>Greenguard</b>                               | -              | Greenguard Gold                           |                        |               |
| <b>VOC Emissions</b>                            | -              | Zero VOC                                  |                        |               |



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Color Body Porcelain Tile
- Matte | Anti-Slip | Finishes
- 9mm | 20mm Thicknesses
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistant

