

Features	Test Method	Value		
Dimensions	ISO 10545 - 2	Compliant		
Surface Quality		Min. 95% of tiles free of visible defects		
Water Absorption	ISO 10545 - 3	≤ 0.1%		
Breaking Strength	ISO 10545 - 4	Matte Anti-Slip		Pavers
		≥ 1500 N		≥ 10000 N
Bending Resistance		≥ 40 N/mm²		≥ 45 N/mm²
Deep Abrasion Resistance	ISO 10545 - 6	≤ 150 mm³		
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	≤ 7 MK ⁻¹		
Thermal Shock Resistance	ISO 10545 - 9	Resistant		
Crazing Resistance	ISO 10545 - 12	Resistant		
Chemical Resistance (Domestic)	ISO 10545 - 13	A		
Chemical Resistance (Low Concentration)		LA		
Chemical Resistance (High Concentration)		HA		
Fire Resistance	-	A1/A1 _{FL}		
Slip Resistance (Wet)	ANSI A326.3	Matte	Anti-Slip	Pavers
		DCOF 0.67	DCOF 0.78	DCOF 0.73
LEED	-	Yes		
Recycled Material	-	10%		
Environmental Product Declaration	-	Product-Specific		
Health Product Declaration	-	Available		
Declare	-	Red List Free		
Greenguard	-	Greenguard Gold		
VOC Emissions	-	Zero VOC		



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Matte | Anti-Slip | Finishes
- 9mm | 20mm Thicknesses
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.