

Features	Test Method	Value	
Length and Width	ISO 10545-2	± 0.2%	
Thickness		± 5%	
Warpage of Edges		± 0.2%	
Wedging		± 0.2%	
Warpage		± 0.2%	
Water Absorption	ISO 10545-3	≤ 0.1%	
Bending Strength	ISO 10545-4	R ≥ 50 N/mm ²	
		S > 1700 N	
Coefficient of Linear Thermal Expansion	ISO 10545-8	6.5x10 ⁻⁶ °C ⁻¹	
Thermal Shock Resistance	ISO 10545-9	Guaranteed	
Frost Resistance	ISO 10545-12	Frost-Proof	
Chemical Resistance	ISO 10545-13	GB Min.	
Stain Resistance	ISO 10545-14	Class 3 Min.	
Slip Resistance	DIN 51130	Natural	Anti-Slip
		R10	R11
Recycled Content	-	> 40%	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Natural | Polished | Anti-Slip Finish
- 9mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes

