

Features	Test Method	Value	
Dimensions	ISO 10545 - 2	Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Water Absorption	ISO 10545 - 3	≤ 0.1 %	
Modulus of Rupture / Bending Strength	ISO 10545 - 4	R ≥ 40 N/mm ²	
Breaking Strength		S ≥ 1500 N	
Deep Abrasion Resistance	ISO 10545 - 6	≤ 150 mm ³	
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	≤ 7MK ⁻¹	
Thermal Shock Resistance	ISO 10545 - 9	Resistant	
Crazing Resistance	ISO 10545 - 11	Resistant	
Chemical Resistance (Domestic)	ISO 10545 - 13	A	
Chemical Resistance (Low Concentration)		LA	
Chemical Resistance (High Concentration)		HA	
Fire Resistance	-	A1/A1 _{FL}	
Slip Resistance (Wet)	ANSI A326.3	Matte	Anti-Slip
		DCOF 0.57	DCOF 0.62
LEED	-	Yes	
Recycled Material	-	10%	
VOC Emissions	-	Zero VOC	
Declare	-	Red List Free	
Environmental Product Declaration	-	Product-Specific	
Health Product Declaration	-	Available	
Greenguard	-	Greenguard Gold	



Declare.

This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain Tile
- Rectified Edge
- Matte | Anti-Slip Finishes
- V3 - Moderate Variation
- 9mm Thickness
- Frost Resistant



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.