

Features	Test Method	Value
Length and Width	ISO 10545 - 2	Compliant
Thickness		Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage	ASTM C485	Compliant
Wedging	ASTM C502	Compliant
Water Absorption	ASTM C373	≤ 0.5 %
Breaking Strength	ASTM C648	≥ 250 lbf
Chemical Resistance (Domestic)	ASTM C650	A
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		HA
Fire Resistance	-	A1/A1 _{FL}
Slip Resistance	ANSI A326.3	
LEED	-	Yes
EPD	-	Yes
Declared	-	Red List Free
Greenguard Gold	-	Yes
VOC Emissions	-	Zero VOC



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:**
- Rectified Edge
 - Color Body Porcelain Tile
 - Matte | Polished Finishes
 - 9mm Thickness
 - V3 - Moderate Variation
 - Frost Resistance - Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.