

Features	Test Method	Value	
Length and Width	ASTM C499	Compliant	
Thickness		Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Warpage	ASTM C485	Compliant	
Wedging	ASTM C502	Compliant	
Water Absorption	ASTM C373	≤ 0.5 %	
Breaking Strength	ASTM C648	≥ 450 lbf	
Thermal Shock Resistance	ASTM C484	Resistant	
Crazing Resistance	ASTM C424	Resistant	
Chemical Resistance	ASTM C650	Not Affected	
Fire Resistance	-	A1/A1 _{FL}	
Slip Resistance (Wet)	ANSI A326.3	Matte	Polished
		DCOF 0.62	Does Not Pass
LEED	-	Yes	
Recycled Content	-	40%	
VOC Emissions	-	Zero VOC	
Declared	-	Red List Free	
Environmental Product Declaration	-	Yes	
Health Product Declaration	-	Available	
Greenguard Gold	-	Yes	
Green Squared	-	Yes	







This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Rectified Edge
- Matte | Polished Finishes
- V3 - Moderate Variation
- 9mm Thickness
- Frost Resistant


www.genrose.com