



Features	Test Method	Value		
Dimensions	ISO 10545 - 2	Compliant		
Surface Quality		Min. 95% of tiles free of visible defects		
Warpage		Compliant		
Wedging		Compliant		
Water Absorption	ISO 10545 - 3	0.08%		
Modulus of Rupture / Bending Strength	ASTM C1505	<b>6mm</b>	<b>9mm</b>	<b>20mm</b>
		52 N/mm <sup>3</sup>	50 N/mm <sup>3</sup>	52 N/mm <sup>3</sup>
Breaking Strength	ASTM C648	1350 N	2200 N	14000 N
Deep Abrasion Resistance	ISO 10545 - 6	140/mm <sup>3</sup>		
Thermal Shock Resistance	ISO 10545 - 9	Resistant		
Chemical Resistance (Domestic)	ISO 10545 - 13	UA		
Chemical Resistance (Low Concentration)		LA		
Chemical Resistance (High Concentration)		HA		
Slip Resistance (WET)	ANSI A326.3	DCOF 0.62		
Recycled Content	-	<b>6mm   9mm</b>	<b>20mm</b>	<b>Slabs</b>
		13.9%	13%-16%	0%-7%
Environmental Product Declaration	-	Industry Wide		
Greenguard Gold	-	Yes		
VOC Emissions	-	Zero VOC		
 		This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Color Body Porcelain Tile
- Matte | Soft | Bushhammered | Anti-Slip Finishes
- 6mm | 9mm | 20mm Thicknesses
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistant

