

Features	Test Method	Value	
Length and Width	ISO 10545 - 2	±0.5%, ±2mm	
Thickness		±5%, ±0.5mm	
Straightness of Sides		±0.5%, ±1.5mm	
Rectangularity		±0.5%, ±1.5mm	
Surface Flatness		±0.5%, ±0.5mm	
Surface Quality		Min. 95% of tiles free of visible defects	
Water Absorption	ISO 10545 - 3	≤ 0.3 %	
Modulus of Rupture / Bending Strength	ISO 10545 - 4	R > 35 N/mm ²	
Breaking Strength		S > 1300 N	
Thermal Shock Resistance	ISO 10545 - 9	Resistant	
Crazing Resistance	ISO 10545 - 11	Resistant	
Chemical Resistance (Domestic)	ISO 10545 - 13	A	
Chemical Resistance (Low Concentration)		LA	
Chemical Resistance (High Concentration)		HA	
Fire Resistance		A1/A1 _{FL}	
Slip Resistance (Wet)	ANSI A326.3	High-Gloss	Matte Pepper Gemstone Terrazzo Deco
		Does Not Pass	DCOF 0.55
LEED	-	Yes	
Recycled Content	-	10%	
VOC Emissions	-	Zero VOC	
Environmental Product Declaration	-	Facility Specific	





This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain Tile
- Matte | Pepper | High Gloss | Matte/Glossy Mix (Decos Only) Finishes
- 10mm Thickness
- Pressed Edge
- V3 - Moderate Variation (Pepper Finish & All Decos)
- V1 - Uniform Appearance
- Frost Resistant



www.genrose.com