

Features	Test Method	Value		
Length and Width	ISO 10545-2	± 0.1 %		
Thickness		± 3.0 %		
Straightness of Sides		± 0.1 %		
Rectangularity		± 0.2 %		
Surface Flatness		± 0.2 %		
Water Absorption	ISO 10545-3	≤ 0.1 %		
Breaking Strength	ISO 10545-4	> 2600 N		
Modulus of Rupture		> 53 N/mm ²		
Abrasion Resistance	ISO 10545-7	5		
Coefficient of Linear Thermal Expansion (1/K)	ISO 10545-8	6.7 x 10 ⁻⁶		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Crazing Resistance	ISO 10545-11	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Chemical Resistance	ISO 10545-13	Household/ Swimming Pool Salts	Low Concentration	High Concentration
		GA	GLA	GHA
DCOF (WET)	ANSI A137.1	R10 /B / Class 2		
Stain Resistance	ISO 10545-14	5		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 8.8mm | 9.2mm | 10mm Thicknesses
- Rectified Edge
- PEI Rating = 5
- V3 - Moderate Variation
- Frost Resistance = Yes


www.genrose.com