

Features	Test Method		Value
Thickness	ISO 10545-2		±5%
Length and Width			±0.60%
Straightness of Sides			±0.50%
Rectangularity			±0.50%
Surface Flatness			±0.50%
Water Absorption			ISO 10545-3
Breaking Strength	ISO 10545-4		≥ 600 N
Modulus Rupture			≥ 12 N/mm2
Thermal Shock Resistance	ISO 10545-11		Resistant
Chemical Resistance	ISO 10545-13	Resistance to low concentrations of acids and bases.	Min T GLB
		Resistance to high concentrations of acids and bases.	Min T GHB
		Resistance to cleaning and swimming pool additives.	Min T3
Stain Resistance	ANSI A137.1		Min T3
Recycled Material	-		38.6%



This product will contribute to USGBC registered LEED projects v4.1.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Wall Tile
- Matte Finish
- 12mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = No



www.genrose.com