

Features	Test Method	Value	
Thickness	ASTM C499	max ± 0.030 in	
Water Absorption	ASTM C373	≤ 0.5%	
Abrasion Resistance	ISO 10545-7	4	
Linear Thermal Expansion	ASTM C372	Conforms	
Thermal Shock Resistance	ASTM C484	Resistant	
Breaking Strength	ASTM C648	9mm - 450 lbf	20mm - 2800 lbf
Chemical Resistance	ASTM C650	Resistant	
Stain Resistance	ASTM C1378	Resistant	
Frost Resistance	ASTM C1026	Resistant	
Bond Strength	ASTM C482	50 PSI	
Surface Hardness	Mohs Scale	7 Mohs	
Warpage Edge	ASTM C485	Conforms	
Warpage Diagonal	ASTM C485	Conforms	
DCOF (WET)	ANSI A326.3	9mm - IW+	20mm - EW
Recycled Material	-	40%	






This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte Finish
- 9mm | 20mm Thicknesses
- Rectified Edge
- Frost Resistance = Yes
- V3 - Moderate Variation
- Application: Residential, Light Commercial



[www.genrose.com](http://www.genrose.com)