

Features	Test Method	Value	
Dimensions	ASTM C499	Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Warpage	ASTM C485	Compliant	
Wedging	ASTM C502	Compliant	
Water Absorption	ASTM C373	≤ 0.5%	
Breaking Strength	ASTM C648	8mm	20mm
		503 lbf	3300 lbf
Deep Abrasion Resistance	ASTM C1027-99	Class IV	
Thermal Shock Resistance	ASTM C484	Resistant	
Crazing Resistance	ASTM C424	Resistant	
Chemical Resistance (Domestic)	ASTM C650	UA	
Chemical Resistance (Low Concentration)		UA	
Chemical Resistance (High Concentration)		UA	
Fire Resistance	-	A1/A1 _{FL}	
Slip Resistance (Wet)	ANSI A326.3	8mm	20mm
		DCOF ≥ 0.54	DCOF ≥ 0.60
LEED	-	Yes	
Recycled Content	-	≥ 28%	
VOC Emissions	-	Zero VOC	
Declare	-	Red List Free	
Environmental Product Declaration	-	Facility-Specific	
Health Product Declaration	-	Available	
Greenguard	-	Greenguard Gold	
Green Squared	-	Yes	



Declare. This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

Minimum grout size recommended = 5 mm (or approx. 3/16") If staggered tile placement, we recommend using a 30% offset. If specified brick pattern with 1/2 pattern mandatory, a bigger grout is recommended to hide imperfections of installation (minimum 1/4").

Product Info:

- Color Body Porcelain Tile
- Matte | Polished Finishes
- 8mm | 20mm | 7mm (Cove Base) Thicknesses
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistant



www.genrose.com