

Features	Test Method	Value		
Length And Width	ISO 10545-2	±0.2%		
Thickness	ISO 10545-2	±5%		
Warpages Of Edges	ISO 10545-2	±0.2%		
Wedging	ISO 10545-2	±0.25%		
Central And Edge Curvature	ISO 10545-2	±0.2%		
Warpage	ISO 10545-2	±0.2%		
Water Absorption	ISO 10545-3	≤ 0.1%		
Bending Strength	ISO 10545-4	≥ 35 N/MM <sup>2</sup>		
Breaking Strength	ISO 10545-4	≥ 1300 N		
Impact Resistance	ISO 10545-5	.85		
Resistance to Deep Abrasion	ISO 10545-6	<145 mm <sup>3</sup>		
Linear Thermal Expansion	ISO 10545-8	Resistant		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Resistance of Chemical Attack	ISO 10545-13	High Concentration	Low Concentration	Domestic Chemicals
		UHA	ULA	UA
Stain Resistance	ISO 10545-14	Class 4		
Color Resistance to Light	DIN 51094	Resistant		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Through Body Porcelain Tile
- Matte | Polished Finishes
- 10mm | 11.5mm Thicknesses
- Rectified Edge
- V1 - Uniform Appearance
- Frost Resistance = Yes


[www.genrose.com](http://www.genrose.com)