

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.3% MAX ± 1mm
Thickness		± 5% MAX ± 0.5mm
Squareness of Corners		± 0.3% MAX ± 1.5mm
Straightness of Sides		± 0.3% MAX ± 0.8mm
Planarity		± 0.4% MAX ± 1.8mm
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	S ≥ 1300 N
Bending Resistance		R ≥ 35 N/mm <sup>2</sup>
Surface Abrasion	ISO 10545-6	4 (All Other Colors) 5 (Black Deco   Saint Laurent)
Thermal Shock Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Resistance to Household Chemicals and Swimming Pool Additives	ISO 10545-13	A
Resistance to Low Concentrations of Acids and Alkali		LA
Stain Resistance	ISO 10545-14	5
Recycled Content	-	18%
This product is certified by Bureau Veritas.		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Polished Finish
- 9mm Thickness
- Rectified Edge
- PEI Rating = 4 (All Other Colors) | 5 (Black Deco | Saint Laurent)
- V2 - Slight Shading Variation
- Frost Resistance = Yes

