




Features	Test Method	Value	
Dimensions and Surface Quality	ISO 10545-2	Complies	
Water Absorption	ISO 10545-3	≤ 0.5 %	
Modulus of Rupture	ISO 10545-4	35 – 45 N/mm ²	
Breaking Strength	ISO 10545-4	1,600 - 2,400 N	
Thermal Resistance	ISO 10545-9	Resistant	
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Polished	Matte
		A, GLB	A, GLA
Stain Resistance	ISO 10545-14	5	
Reaction to Fire	EN14411:2012	A1 _{FL} /A1	
DCOF (Wet)	-	Polished	Matte
		≤ 0.42 Does Not Pass	≥ 0.42
Recycled Material	-	31%	

This product will contribute to USGBC registered LEED V4.1 projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain Tile
- Matte | Polished Finishes
- 9.5mm | 10.5mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- Frost Resistance = Yes
- V3 - Moderate Variation



www.genrose.com