

Features	Test Method	Value
Dimensions	ISO 10545 - 2	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	0.0295 %
Modulus of Rupture/Bending Strength	ISO 10545 - 4	36.04 N mm <sup>2</sup>
Breaking Strength		1864.70 N
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	2.49 x 10 <sup>-6</sup>
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	A
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		HA
Fire Resistance	-	A1/A1 <sub>FL</sub>
Slip Resistance	ANSI A326.3	DCOF <b>Does Not Pass</b>
VOC Emissions	-	Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Glazed Porcelain
- Carved | Matte | Polished Finishes
- 8.5mm Thickness
- V2 - Slight Shade Variation
- Rectified Edge
- Frost Resistance = Yes

