

Features	Test Method	Value	
		Polished	Matte
Length and Width	ISO 10545 - 2	± 0.1 %	
Thickness		± 5.0 %	
Straightness of Sides		± 0.1 %	
Rectangularity		± 0.1 %	
Surface Flatness		± 0.2 %	
Glossiness	Glossometer	min 90%	min 4%
Water Absorption	ISO 10545 - 3	≤ 0.20 %	
Flexural Strength	ISO 10545 - 4	≥ 40 N mm ²	
Breaking Strength		> 1500 N	
Impact Resistance	ISO 10545 - 5	Min 0.55	
Apparent Density	DIN 51082	> 2.10 g/cc	
Mohs Hardness	EN 101	≥ 4	≥ 5
Surface Abrasion Resistance	ISO 10545-7	Min Class 3	Min Class 4
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	6.5 x 10-6 Max	
Thermal Shock Resistance	ISO 10545 - 9	No Change	Passed
Moisture Expansion	ISO 10545 - 10	-	Passed
Crazing Resistance	ISO 10545 - 11	Min 10 Cycle	
Frost Resistance	ISO 10545 - 12	Resistant	
Chemical Resistance	ISO 10545 - 13	Resistant	
Stain Resistance	ISO 10545 - 14	Resistant	
Slip Resistance Coefficient of Friction	ISO 10545 - 17	≥ 0.4	
DCOF Wet and Dry	-	> 0.40 WET < 0.40 Dry	
Low Emissions Material • Zero VOC			

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain
- Carved | Matte | Polished Finishes
- 8.5mm Thickness
- Rectified Edge
- Frost Resistance = Yes


www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.