

Features	Test Method	Value
Length and Width	ISO 10545 - 2	±0.9
Thickness		±0.5
Linearity		±0.75
Wedging		±0.75
Warpage		±0.75
Water Absorption	ISO 10545 - 3	$E \leq 0.5\%$
Modulus of Rupture	ISO 10545 - 4	$\geq 35 \text{ N/mm}^2$
Breaking Strength		$\geq 1300 \text{ N}$
Impact Resistance	ISO 10545 - 5	0.87
Abrasion Resistance	ISO 10545 - 7	2 - 4
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	$6.5 \times 10^{-6}/^{\circ}\text{C}$
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Moisture Expansion	ISO 10545 - 10	0.1 mm/m
Crazing Resistance	ISO 10545 - 11	Resistant
Frost Resistance	ISO 10545 - 12	Resistant
Resistance to Chemicals	ISO 10545 - 13	Min Class B
Resistance to Staining	ISO 10545 - 14	Min Class 3
Reaction to Fire	ISO 10545 - 15 UNI EN ISO13501/1	Class A1-A1 _{FL}
Slip Resistance	DIN 51130	R10
	ANSI DCOF A137.1-2012	0.64
Low Emissions Material • Zero VOC		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Porcelain Tile
- Matte Finish
- 9mm Thickness
- Rectified Edge
- PEI Rating = 4
- V2 - Slight Shading Variation
- Frost Resistance = Yes



www.genrose.com