

Features	Test Method	Value
Dimensions-Length and Width	UNI EN ISO 10545-2	± 0.6% MAX ± 2.0 mm
Side Straightness	UNI EN ISO 10545-2	± 0.5% MAX ± 1.5 mm
Corner Squareness	UNI EN ISO 10545-2	± 0.5% MAX ± 2.0 mm
Flatness	UNI EN ISO 10545-2	± 0.5% ± 2.0 mm
Thickness	UNI EN ISO 10545-2	± 5% MAX ± 0.5 mm
Water Absorption	UNI EN ISO 10545-3	≤ 0.5%
Breaking Strength	UNI EN ISO 10545-4	≥ 1300 se sp ≥7.5 mm ≥ 700 se sp <7.5 mm
Modulus of Rupture	UNI EN ISO 10545-4	≥ 35 N/mm ²
Stain Resistant	UNI EN ISO 10545-14	3
Resistance to Chemicals for Household Use	UNI EN ISO 10545-13	B MIN
Frost Resistance	UNI EN ISO 10545-12	Resists
Coeff. of Linear Thermal Expansion	UNI EN ISO 10545-8	7.0° MK (-1)
Thermal Shock Resistance	UNI EN ISO 10545-9	Request
Color Stability	DIN 51094	Resists

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Polished | Natural | Anti-Slip Finishes
- 10mm Thicknesses
- Rectified Edge
- PEI Rating = 3
- Frost Resistance = Yes
- V3 - Moderate Variation