

MONTAUK

				U 1
Color	Body	Porce	lain	Tile

Features	Test Method	Value			
Dimensions		Compliant			
Surface Quality	ISO 10545 - 2	Min. 95% of tiles free of visible defects			
Water Absorption	ISO 10545 - 3	< 0.1%			
Modulus of Rupture / Bending Strength	ISO 10545 - 4	9mm 20mm		20mm	
		> 35 N/n	> 35 N/mm ² 60.4 N/m		
Breaking Strength		≥ 1,300	≥ 1,300 N		
Deep Abrasion Resistance	ISO 10545 - 6	≤ 150 m	m ³	≤ 130 mm ³	
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	< 7.1 10 ⁻⁶ °C ⁻¹			
Thermal Shock Resistance	ISO 10545 - 9	Resistant			
Crazing Resistance	ISO 10545 - 11	Resistant			
Chemical Resistance (Domestic)		A LA			
Chemical Resistance (Low Concentration)	ISO 10545 - 13				
Chemical Resistance (High Concentration)		НА			
Fire Resistance	-	A1/A1 _{FL}			
Slip Resistance	ANSI A326.3	9mm Matte	9mm Anti-Slip	20mm Anti-Slip	
		DCOF 0.61	DCOF 0.60	DCOF 0.61	
LEED	-	Yes			
Recycled Content	-	> 30%			
VOC Emissions	_	Zero VOC			
Declare	_	Red List Free			
Environmental Product Declaration	-	Industry-Wide			
Health Product Declaration	-	Available			
	This	product will contrid	cute to USGBC regis	stered LEED projects.	

Declare. It will also contricute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

N SY

- Color Body Porcelain Tile
- Matte | Anti-Slip Finishes
- 6mm | 9mm | 20mm Thickness

- Rectified Edge
- V3 Moderate Variation
- Frost Resistance Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.