

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.6% MAX ± 2mm
Straightness of Sides		± 0.5% MAX ± 1.5mm
Corner Squareness		± 0.5% MAX ± 2mm
Flatness		± 0.5% ± 2mm
Thickness		± 0.5% MAX ± 0.5mm
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	≥ 1300 N ≥ 7.5mm ≥ 700 N < 7.5mm
Modulus of Rupture		≥ 35 N/mm ²
Coefficient of Linear Thermal Expansion	ISO 10545-8	7° MK (-1)
Frost Resistance	ISO 10545-12	Resistant
Resistance to Household Chemicals	ISO 10545-13	B MIN
Stain Resistance	ISO 10545-14	3
Color Stability	DIN 51094	Resistant

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Natural | Polished Finish
- 9mm Thickness
- Rectified Edge
- PEI Rating = 5
- V2 - Slight Shading Variation
- Frost Resistance = Yes

