




Features	Test Method	Value
Length and Width	ISO 10545-2	Compliant
Thickness		Compliant
Straightness of Sides		Compliant
Surface Flatness		Compliant
Water Absorption	ISO 10545-3	$\leq 0.5\%$
Modulus of Rupture/ Bending Strength	ISO 10545-4	$\geq 35 \text{ N/mm}^2$
Breaking Strength		$\geq 1300\text{N}$
Thermal Shock Resistance	ISO 10545-9	Resistant
Chemical Resistance (Domestic)	ISO 10545-13	A
Chemical Resistance (Low Concentration)		LA
Reaction to Fire	-	A1/ A1 <sub>FL</sub>
Slip Resistance	ANSI A326.3:2021	DCOF 0.46
LEED	-	Yes
Recycled Material	-	8%
VOC Emissions	-	Zero VOC
Environmental Product Declaration	-	Industry-Wide
   <p style="text-align: right;">This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

#### Product Info:

- Glazed Porcelain Tile
- Natural Finish
- 9mm Thickness
- PEI Rating = 4 (House | Jazz); 2 (Blues)
- Rectified Edge
- Frost Resistance = Yes



**www.genrose.com**