


| Features                                 | Test Method    | Value  |
|--|----------------|--|
| Dimensions                               | ISO 10545 - 2  | Compliant  |
| Surface Quality                          |                | Min. 95% of tiles free of visible defects                |
| Water Absorption                         | ISO 10545 - 3  | < 0.15%  |
| Modulus of Rupture / Bending Strength    | ISO 10545 - 4  | ≥ 35 N/mm <sup>2</sup>                                   |
| Coefficient of Linear Thermal Expansion  | ISO 10545 - 8  | $a \leq 7.1 \times 10^{-6} \text{ } ^\circ\text{C}^{-1}$ |
| Thermal Shock Resistance                 | ISO 10545 - 9  | Resistant  |
| Crazing Resistance                       | ISO 10545 - 11 | Resistant  |
| Chemical Resistance (Domestic)           | ISO 10545 - 13 | A  |
| Chemical Resistance (Low Concentration)  |                | LA   |
| Chemical Resistance (High Concentration) |                | HA   |
| Fire Resistance                          | -              | A1/A1 <sub>FL</sub>                                      |
| LEED                                     | -              | Yes  |
| Recycled Content                         | -              | ≥ 30%  |
| VOC Emissions                            | -              | Zero VOC   |
| Material Health Certification            | -              | Red List Free, Certificate Available                     |
| Environmental Product Declaration        | -              | Facility-Specific  |



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Glazed Porcelain Tile
- Natural Finish
- 8.5mm Thickness
- Rectified Edge
- V2 - Slight Variation
- Frost Resistance - Yes



[www.genrose.com](http://www.genrose.com)