

Features	Test Method	Value	
Length and Width	ASTM C499	± 0.25%	
Thickness		± 0.04 in	
Surface Quality		Min. 95% of tiles free of visible defects	
Warpage	ASTM C485	± 0.75%	
Wedging	ASTM C502	± 0.50%	
Water Absorption	ASTM C373	≤ 0.5%	
Breaking Strength	ASTM C648	≥ 300 lbf	
Visible Abrasion Resistance	ASTM C1027-99	Class IV	
Thermal Shock Resistance	ASTM C484	Resistant	
Crazing Resistance	ASTM C424	Resistant	
Chemical Resistance (Domestic)	ASTM C650	Not Affected	
Chemical Resistance (Low Concentration)		Not Affected	
Chemical Resistance (High Concentration)		Not Affected	
Fire Resistance	-	A1/A1 _{FL}	
Slip Resistance (Wet)	ANSI A326.3	Matte	Anti-Slip
		DCOF 0.42	DCOF 0.76
LEED	-	Yes	
Recycled Content	-	≥ 65%	
VOC Emissions	-	Zero VOC	
Declare	-	Red List Free	
Environmental Product Declaration	-	Product Specific	
Health Product Declaration	-	Available	
Greenguard	-	Greenguard Gold	
Green Squared	-	Yes	


Declare.

This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain Tile
- Rectified | Pressed Edges
- Matte | Anti-Slip Finishes
- V2 - Slight Variation
- 7mm | 8mm Thicknesses
- Frost Resistant


www.genrose.com