

Features	Test Method	Value
<b>Length and Width</b>	ISO 10545-2	±0.6% / ±2.0mm
<b>Thickness</b>	ISO 10545-2	±5% / ±0.5mm
<b>Straightness of Sides</b>	ISO 10545-2	±0.5% / ±1.5mm
<b>Rectangularity</b>	ISO 10545-2	±0.5% / ±2.0mm
<b>Surface Flatness</b>	ISO 10545-2	±0.5% / ±2.0mm
<b>Surface Quality</b>	ISO 10545-2	95% of Tiles with No Defaults
<b>Water Absorption</b>	ISO 10545-3	≤0.5% Maximum Single Value
<b>Average Bending Strength</b>	ISO 10545-4	35 N/mm <sup>2</sup>
<b>Breaking Strength</b>	ISO 10545-4	≥ 7.5 mm: 1300 N Min < 7.5 mm: 700 N Min
<b>Resistance to Surface Abrasion</b>	ISO 10545-7	4
<b>Crazing Resistance</b>	ISO 10545-11	Resistant
<b>Frost Resistance</b>	ISO 10545-12	Resistant
<b>Chemical Resistance</b>	ISO 10545-13	GB Min
<b>Stain Resistance</b>	ISO 10545-14	Class 3 Min
<b>Coefficient of Friction</b>	B.C.R.A. Method	Matte: Dry: > 0.40 Wet: > 0.40
<b>Antislip Properties</b>	DIN 51130	Matte: R9
<b>Dynamic Coefficient of Friction</b>	DCOF ANSI A137-1:2012	Matte: Wet: > 0.42

This product will contribute to USGBC registered LEED projects.  
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.  
 Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte | Polished Finishes
- 10mm Thickness
- Rectified Edge
- Frost Resistance = Yes
- PEI Rating = 4
- V2 - Slight Shading Variation



[www.genrose.com](http://www.genrose.com)