



Features	Test Method	Value
Dimensions	ISO 10545 - 2	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	$\leq 0.6\%$
Modulus of Rupture / Bending Strength	ISO 10545 - 4	42.5 N/mm <sup>2</sup>
Breaking Strength		1300 N
Deep Abrasion Resistance	ISO 10545 - 6	175 mm <sup>3</sup>
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	UB Min
Fire Resistance	-	A1/A1 <sub>FL</sub>
Slip Resistance (Wet)	ANSI A326.3	DCOF 0.43
Recycled Content	-	5%
VOC Emissions	-	Zero VOC
Material Health Certification	-	Red List Free, Certificate Available
Environmental Product Declaration	-	Industry-Wide
Health Product Declaration	-	Available
 		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Color Body Porcelain Tile
- Matte | Polished Finishes
- 10mm Thickness
- Rectified Edge
- Frost Resistance = Yes
- V2 - Slight Shading Variation


[www.genrose.com](http://www.genrose.com)