

Features	Test Method	Value
Dimensions	ASTM C499	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage	ASTM C485	±0.4%
Wedging	ASTM C502	±0.4%
Water Absorption	ASTM C373	≤ 0.25%
Modulus of Rupture / Bending Strength	ASTM C1505	5000 psi
Breaking Strength	ASTM C648	2000 lbf
Thermal Shock Resistance	ASTM C484	Resistant
Crazing Resistance	ASTM C424	Resistant
Chemical Resistance (Domestic)	ASTM C650	UA
Slip Resistance	ANSI A326.3	DCOF 0.71
LEED	-	Yes
Environmental Product Declaration	-	Yes
Health Product Declaration	-	Yes
Green Squared	-	Yes
Declared	-	Red List Free
VOC Emissions	-	Zero VOC
Material Health Certification	-	Red List Free, Certificate Available



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Anti-Slip Finish
- 20mm Thickness
- Rectified Edge
- V1 - Uniform Appearance
- V2 - Slight Variation
- V3 - Moderate Variation
- V4 - Extreme Variation
- Frost Resistant

