

Features	Test Method	Value
Dimensions	ASTM C499	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage	ASTM C485	Compliant
Wedging	ASTM C502	Compliant
Water Absorption	ASTM C373	< 0.5%
Breaking Strength	ASTM C648	≥ 3000 lbs
Surface Hardness (Mohs)	ASTM C648	6
Thermal Shock Resistance	ASTM C1026	Compliant
Crazing Resistance		Compliant
Chemical Resistance (Domestic)	ASTM C650	Compliant
Chemical Resistance (Low Concentration)		
Chemical Resistance (High Concentration)		
Slip Resistance (Wet)	ANSI A326.3	DCOF ≥ 0.7
Recycled Content	-	5%
Health Product Declaration	-	Certificate Available
Environment Product Declaration	-	Yes
Declare	-	Red List Free
LEED	-	Yes
VOC Emissions	-	Zero VOC



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Porcelain Paver
- Anti-Slip Finish
- 20mm Thickness
- Rectified Edge
- V2 - Slight Variation
- V3 - Moderate Variation (Pennsylvania Blue only)
- Frost Resistant



www.genrose.com