


Features	Test Method	Value	
Dimensions	ASTM C499	Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Warpage	ASTM C485	± 0.40%	
Wedging	ASTM C502	± 0.25%	
Water Absorption	ASTM C373	≤ 0.5%	
Breaking Strength	ASTM C648	≥ 275 lbf	
Thermal Shock Resistance	ASTM C484	Resistant	
Crazing Resistance	ASTM C424	Resistant	
Chemical Resistance (Domestic)	ASTM C650	Not Affected	
Chemical Resistance (Low Concentration)			
Chemical Resistance (High Concentration)			
Slip Resistance (DCOF)	ANSI A326.3	Semi-Polished	Structured
		Does Not Pass	0.47
LEED	-	Yes	
Recycled Content	-	≥ 40%	
Green Squared	-	Yes	
Greenguard	-	Greenguard Gold Certificate Available	
Declare	-	Red List Free	
VOC Emissions	-	Zero VOC	








This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain Tile
- 8mm Thickness
- Semi-Polished | Structured Finishes
- Rectified Edge
- PEI Rating: 3,4 (Vary By Color)
- V2 - Moderate Variation
- Frost Resistant



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.