





Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.3%, max ± 1mm
Thickness		± 5%, max ± 0.5mm
Straightness of Sides		± 0.3%, max ± 0.8mm
Rectangularity		± 0.3%, max ± 1.5mm
Warpage		± 0.4%, max ± 1.8mm
Water Absorption	ISO 10545-3	0.05%
Modulus of Rupture / Bending Strength	ISO 10545-4	50 N/mm ²
Breaking Strength		2200 N
Resistance to Surface Abrasion	ISO 10545-6	145mm ³
Coefficient of Linear Thermal Expansion	ISO 10545-8	$\alpha \leq 7 \cdot 10^{-6} \text{ }^{\circ}\text{C}^{-1}$
Thermal Shock Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance (Domestic)	ISO 10545-13	Class A
Chemical Resistance (Low)		LA, HA
Chemical Resistance (High Concentration)		LA, HA
Stain Resistance	ISO 10545-14	Class 5
Slip Resistance	ANSI A326.3	DCOF 0.62
Recycled Content	-	40% Pre-Consumer

This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
 Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Worn Finish
- 9.5mm Thickness
- Rectified Edge
- V3 - Moderate Variation = White | Gray
- V4 - **Extreme** Variation = Desert | Earth
- Frost Resistance = Yes



www.genrose.com