

Features	Test Method	Value
Length and Width	ISO 10545-2	≤2% or max 5mm
Thickness	ISO 10545-2	±5% or ±0.5mm
Side Straightness	ISO 10545-2	±0.5% or ±1.5mm
Rectangularity	ISO 10545-2	±0.5% or ±2mm
Surface Flatness	ISO 10545-2	±0.5% or ±2mm
Superficial Quality	ISO 10545-2	95%
Water Absorption	ISO 10545-3	≤ 0.5
Modulus of Rupture	ISO 10545-4	≥35 N/mm ≥1300 N
Abrasion Resistance	ISO 10545-7	4
Thermal Shock Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance - Household	ISO 10545-13	GA
Chemical Resistance - High Concentration	ISO 10545-13	GHA
Chemical Resistance - Low Concentration	ISO 10545-13	GLA
Resistance to Staining	ISO 10545-14	Class 5

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Porcelain Tile
- Matte Finish
- 9.3mm Thickness
- Pressed Edge
- PEI Rating = 4
- V3 - Moderate Variation
- Frost Resistance = Yes

