

Features	Test Method	Value
Length / Width	EN ISO 10545 - 2	$\leq \pm 0.25\%$
Thickness		$\pm 2.5\%$
Straightness of Side		$\pm 0.15\%$
Rectangularity		$\pm 0.4\%$
Surface Flatness		$\pm 0.3\%$
Water Absorption		EN ISO 10545 - 3
Weight / M ²	-	6.5mm Thick 11.50 kg
Modulus of Rupture	EN ISO 10545 - 4	$\geq 25 \text{ N / mm}^2$
Thermal Shock	EN ISO 10545 - 9	Pass
Crazing Resistance	EN ISO 10545 - 11	Pass
Frost Resistance	EN ISO 10545 - 12	Not Suitable
Chemical Resistance	EN ISO 10545 - 13	Class A - B
Stain Resistance	EN ISO 10545 - 14	Class 3
Fire Rating	-	Class A1 Non Combustible
Recycled Material		$\leq 20\%$

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



Product Info:

- Ceramic Tile
- Gloss | Satin Finishes
- 6.5mm Thickness
- V1 - Uniform Variation
- Frost Resistance = No



www.genrose.com