

Features	Test Methods	Required Value	Our Value
Length and Width	ISO 10545-2	± 0.6% / ± 2 mm	± 0.6% / ± 2 mm
Thickness	ISO 10545-2	± 5%	± 5%
Warpage of Edges	ISO 10545-2	± 0.5%	± 0.5%
Wedging	ISO 10545-2	± 0.6%	± 0.6%
Warpage	ISO 10545-2	± 0.5%	± 0.5%
Water Absorption	ISO 10545-3	<0.5%	0.3%
Resistance to Thermal Shock	ISO 10545-9	Must not produce noticeable alteration to surface	Guaranteed
Frost Resistance	ISO 10545-12	Must not produce noticeable alteration to surface	Guaranteed
Chemical Resistance	ISO 10545-13	Must not produce noticeable alteration to surface	A LA HA
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²	42 N/mm ²
Resistance to Abrasion	ISO 10545-7		PEI 5
Stain Resistance	ISO 10545-14	≥Class 3	4
Anti-Slip	DIN 51130		R9
Dynamic Coefficient of Friction	DCOF	>0.42	0.42

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 9.5mm Thickness
- Rectified Edge
- PEI Rating = 5
- V1 - Uniform Appearance
- Frost Resistance = Yes

