

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.6% (±2.00mm)
Thickness		± 5% (±0.5mm)
Warpage		± 0.5% (±1.5mm)
Wedging		± 0.5% (±2.00mm)
Flatness		± 0.5% (±2.00mm)
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	S>1300 N
Bending Strength	ISO 10545-4	R ≥ 35 N/mm ²
Coefficient of Linear Thermal Expansion	ISO 10545-8	≈7 x 10 ⁻⁶ C ⁻¹
Thermal Shock Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Resistant
Stain Resistance	ISO 10545-14	≥ Class 3
Color Resistance to Light	DIN 51094	No Alteration
Slip Resistance	ASTM C-1028	Dry/Wet >0.6

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte | Polished Finish
- 9.5mm Thickness
- Rectified | Pressed Edge
- Frost Resistance = Yes
- V4 - **EXTREME** Variation

