

Features	Test Method	Value		
		12x24	24x48	
Dimensions and Appearance	ISO 10545-2	Prospect G.1		
Water Absorption	ISO 10545-3	≤ 0.10 %		
Bending Strength	ISO 10545-4	≥ 45 N/MM ²		
Breaking Strength	ISO 10545-4	S ≥ 1300 N		
Resistance to Deep Abrasion	ISO 10545-6	<140 mm ³		
Linear Expansion Thermal Coefficient	ISO 10545-8	≤ 7 x 10 ⁻⁶ °C ⁻¹		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Resistance of Chemical Attack	ISO 10545-13	High Concentration	Low Concentration	Domestic Chemicals
		Available Method	LA, LA/B, LA/C	A
Stain Resistance	ISO 10545-14	5		
Slip Resistance	ANSI 137.1-2012 DCOF	> 0.42	-	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

Product Info:

- Through Body Porcelain Tile
- Matte | Polished Finishes
- 10.5mm Thicknesses
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes

