

Features	Test Method	Fixed Value
Length And Width	ISO 10545-2	± 0.6% (± 2.00 mm)
Thickness		± 5% (± 0.5 mm)
Warpages Of Edges		± 0.5% (± 1.5 mm)
Wedging		± 0.5% (± 2.00 mm)
Flatness		± 0.5% (± 2.00 mm)
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	≥ 35 N/ mm ²
Breaking Strength		> 1300 N
Coefficient of Linear Thermal Expansion	ISO 10545-8	≈ 7X10 ⁻⁶ C ⁻¹
Thermal Shock Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Resistance of Chemical Attack	ISO 10545-13	Resistant
Stain Resistance	ISO 10545-14	Class 3
Colors Resistance to Light	DIN 51094	No Alteration
Slip Resistance	ANSI 137.1-2012 DCOF	> 0.42
Recycled Content	-	≥ 10

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 9.5 mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- PEI Rating 5
- Frost Resistance = Yes

