





Features	Test Method	Value
Surface Quality	ISO 10545 - 2	Min. 95% of tiles free of visible defects
Water Absorption	ASTM C373	≤ 0.05%
Modulus of Rupture / Bending Strength	ASTM C1505	≥ 45/mm ²
Deep Abrasion Resistance	ISO 10545 - 6	≤ 127mm ³
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	≥ B
Chemical Resistance (Low Concentration)		≥ LB
Fire Resistance	-	A1/A1 _{FL}
LEED	-	Yes
Recycled Content	-	> 40%
VOC Emissions	-	Zero VOC
Declare	-	Red List Free
Environmental Product Declaration	-	Yes
Cradle to Cradle	-	Silver
Greenguard	-	Greenguard Gold

Declare.

This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Porcelain Slabs | Vein Through Porcelain Slabs
- Cashmere | Polished | Natural | Structured Finishes
- 12mm | 20mm Thickness
- Non-Rectified Edge
- Frost Resistant
- Check Decor 24 for Stock

