

Features	Test Method	Value	
Water Absorption	ISO 10545-3	< 0.1%	
Flexural Resistance	ISO 10545-4	> 45 N/mm ²	
Modulus of Rupture	ISO 10545-4	S ≥ 700 N	
Deep Abrasion Resistance	ISO 10545-6	<140 mm ³	
Linear Expansion Thermic Coefficient	ISO 10545-8	≤7x10 ⁻⁶ °C ⁻¹	
Resistance To Sudden Temperature Changes	ISO 10545-9	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Household	Low Concentration
		Class A	LB
Stain Resistance	ISO 10545-14	5	
DCOF (WET)	ANSI B101.3	≥ 0.45	



This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Polished Finish
- 6.5mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes



www.genrose.com