

Features	Test Method	Value	
Dimensions	ISO 243337:2006	7" W x 48" H	
Thickness	EN ISO 24346	0.2" (5 mm)	
Thickness Tolerance of Wear Layer	EN ISO 24340	+13%, -10%	
Wear Resistance	EN 13329:Annex E	Class 33 Heavy Commercial Traffic	
Formaldehyde Emission	EN 12149:1997 Test C	Unit: mg/m ³	Not Detected
Vinyl Chloride Monomer	EN 12149:1997 Test B	Unit: mg/kg	Not Detected
Soluble Cadmium	EN 71-3:1994+AC:2002	Unit: mg/m ³	Not Detected
DEHP+BBP+DBP	EN 14372	Not Detected	
DNOP+DIDP+DINP		Not Detected	
Slip Resistance	DIN 51130:2014	≥ R10	
Fire Resistance	EN 13501-1	Class B1 (B- s1,t0)	
Residual Indentation	ISO 24343-1:2012	≤ 0,1 mm	
Peeling Strength	ISO 24345	≥ 70 N/50mm	
Click Tension Force	ISO 24334	≥ 3 kN/m	
Resistance to Staining	EN 26987	No Contamination or Corrosion	
Curling After Exposure to Heat	ISO 23999	≤ 1 mm	
Dimensional Stability	ISO 24337:2006	≤ 0,15 %	
Installation Gap of Click Flooring		≤ 0,15 mm	

Product Info:

- SPC Click Vinyl Plank Flooring
- 5 mm Thickness
- Matte Finish
- 20 mil (0.5 mm) Wear Layer
- 30 Year Limited Guarantee: Residential
- 15 Year Limited Guarantee: Commercial

