

Features	Test Method	Value
<b>Water Absorption</b>	ANSI / ISO - (%)	10% ≤ E ≤ 16%
<b>Breaking Strength</b>	ANSI - (lbf)	> 128 > 570
<b>Scratch Hardness</b>	ANSI / ISO (Mohs)	4
<b>Abrasion Resistance</b>	ANSI / ISO	Class 0
<b>Frost Resistance</b>	ANSI / ISO	Not Resistant
<b>Chemical Resistance</b>	ANSI / ISO	Class A
<b>Stain Resistance</b>	ANSI / ISO	Class A Class 5
<b>DCOF Slip Resistance</b>	ANSI - Wet ISO - R Value	N/A
<b>Shade Variation</b>	-	V1
Low Emissions Material • Zero VOC		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Ceramic Tile
- Matte | Glossy Finishes
- 7mm | 7.5mm | 7.8mm Thicknesses
- Pressed Edge
- V1 - Uniform Appearance
- Frost Resistance = No

