

Features	Test Method	Value	
Dimensions and Surface Quality	ISO 10545-2	Complies	
Water Absorption	ISO 10545-3	≤ 0.5 %	
Modulus of Rupture	ISO 10545-4	35 – 45 N/mm ²	
Breaking Strength	ISO 10545-4	1,600 - 2,400 N	
Thermal Resistance	ISO 10545-9	Resistant	
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Polished	Matte
		A, GLB	A, GLA
Stain Resistance	ISO 10545-14	5	
Reaction to Fire	EN 14411:2012	A1 _{FL} /A1	
DCOF (Wet)	-	Non-Compliant	
Recycled Material	-	31%	



This product will contribute to USGBC registered LEED V4.1 projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Porcelain Tile
- Matte | Polished Finish
- 10.5mm | 9.5mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- Frost Resistance = Yes
- V3 - Moderate Variation



www.genrose.com